

**SPECIAL
WEB PRICING**

LIMITED TIME *Offers!*



CO-AX CENTERING INDICATORS

Provides a simplified method of centering a workpiece or fixture on horizontal or vertical machines, internal or external diameters. Face of indicator remains stationary in any desired position while the machine spindle rotates, leaving the operator with both hands free to accurately position the machine table.

- Length: 5 1/2" / 140 mm, Shank Dia.: 3/8" / 10 mm, Feeler Dia.: 1/8" / 3 mm.
- 0.25" / 6 mm off-axis measuring range.
- Dial Reading: 0 - 50
- Dial Dia.: 1.60"
- Locating Accuracy within 0.0002" / 0.005 mm of true center.
- Operating speed not to exceed 800 RPM.
- Capacity: 5/32" - 12" / 4 mm - 300 mm Internal, up to 12" / 300 mm External.
- Graduations: 0.0005" / 0.01 mm.
- Kit includes one each of all individual replacement parts listed below.



SAVE UP TO
20%



98-219-9
Super Stop sold separately.

DESCRIPTION	PART NO.	LIST	SALE
Inch Centering Indicator Kit	13-978-2	\$222.40	\$177.92
Metric Centering Indicator Kit	13-979-0	222.40	177.92

Replacement Parts

DESCRIPTION	PART NO.	LIST	SALE
6 Pc Feeler Set (ID, OD)	14-137-4	\$97.65	\$86.90
ID Feeler, 2" long, 4" capacity	14-138-2	19.45	17.31
ID Feeler, 4" long, 8" capacity	14-139-0	19.45	17.31
ID Feeler, 6" long, 12" capacity	14-140-8	19.45	17.31
OD Feeler, 2" long, 4" capacity	14-141-6	19.45	17.31
OD Feeler, 4" long, 8" capacity	14-142-4	19.45	17.31
OD Feeler, 6" long, 12" capacity	14-143-2	19.45	17.31
Center Locating Feeler	14-144-0	24.15	21.49

NEW

SAVE UP TO
15%

IP54 DIGITAL TIRE TREAD GAGE

- Range: 0 - 1" / 25 mm
- Large display:
 - Inch: 0.0005"
 - Metric: 0.01 mm
 - Fraction: 1/32"
- Accuracy: 0.0015"
- Spring loaded movement.
- Hold reading function.
- Auto shut-off after 5 minutes.
- Rod dia.: 3/32"
- Base: 2" L x 1/4" W
- Battery: CR2032 included.
- Plastic pouch included.
- D.O.T. regulated. Shipped via ground freight only. No UPS Consignee or Collect shipments.
- 2 year warranty.

Accessories

DESCRIPTION	PART NO.	PRICE
Repl. Battery (CR2032)	07-319-7	\$2.55



\$30.54
25-367-4
(List \$35.95)

Ground Ship
ONLY



3 SPEED 20" PEDESTAL FAN

Great for Home, Office,
Reception Area and Store

- Tubular steel stand with round base needs little floor space.
- Polypropylene blade is impact and chemical resistant.
- Front steel fan guard snaps into plastic rear grill and needs no clips.
- Height adjusts from 40" to 51" from floor to center of the fan.
- 5' grounded, 3-conductor cord.
- ETL certificate.
- Easy assembly.
- 3 blades.



90-525-7

BLADE SIZE	H.P.	CFM	PART NUMBER	LIST	SALE
20"	1/3	2825/3530/4590	90-525-7	\$123.76	\$111.38

IP54 DIGITAL ROTOR GAGE

- Range: 0 - 3" / 75 mm
- Accuracy: ±0.0015" / .03 mm
- Repeatability: 0.001" / .01 mm
- Large display:
 - Inch: 0.0005"
 - Metric: 0.01 mm
 - Fraction: 1/64"
- ABS button.
- Zero button.
- Jaw depth: 3.5"
- Auto shut-off after 5 minutes.
- Battery: CR2032 included.
- Furnished in fitted case.
- D.O.T. regulated. Shipped via ground freight only. No UPS Consignee or Collect shipments.
- 2 year warranty.

Accessories

DESCRIPTION	PART NO.	PRICE
Repl. Battery (CR2032)	07-319-7	\$2.55



NEW

Ground Ship
ONLY

\$79.94
25-364-1
(List \$99.95)

SAVE UP TO
20%

Offer expires 8/31/2019
Subject to quantities on hand.

Sale prices valid in the USA and Canada only.

**Mention
"Summer PROMO"
When Ordering
From an Authorized
SPI Dealer**



WARNING: Products identified herein may expose you to chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Before purchasing any product identified herein, please consult www.swissprec.com to review any product-specific warnings.